

## LipuJet-P-OAP

### Product information for the product group




#### ACO Product benefits

- Grease separator according to EN 1825 for installation inside frost-free rooms
- Manufactured of polyethylene in oval shape
- Two covers odour-proof Ø 450 mm
- Inlet and outlet Ø 200 mm (NS 15 – 25) or Ø 250 mm (NS 30)
- With two inspection windows for sludge and grease control
- With two high pressure spray heads for perfect inner body cleaning
- Disposal pump for maximum lift heights up to 18 meters with 10 m³/h disposal performance
- Control unit with presets and flexible adjustments (cleaning and filling times)
- Automatically operated disposal pump (3,7 kW) with shut-off valve, disposal connection Ø 75 mm with Storz-B coupling R 2½"
- Two automatically operated high pressure pumps (3,9 kW each) and connection high pressure spray heads (150 bar) for combined mixing of the content and cleaning of the tank
- Automatically operated filling device R ¾" via solenoid valve
- Two inspection windows with wiper
- Operating side left or right

### Item Technical Data 3820.85.42

Nominal capacity	Contents			Operation side
	Sludge trap [l]	Grease store [l]	Overall [l]	
NS 20	2070	850	3760	Right-hand


## Dimensions



Nominal capacity	Dimensions						
	L1 [mm]	H1 [mm]	H2 [mm]	H3 [mm]	H4 [mm]	W1 [mm]	W2 [mm]
NS 20	3910	2090	1640	1300	1230	1530	1260

## Accessories

	Description	Used with	Description	Item number
	Inlet valve DN 200		■ Weight: 8.4 kg	0170.20.83

	Description	Used with	Description	Item number
	Grease layer thickness measuring device	<ul style="list-style-type: none"> <li>■ LipuJet-P <ul style="list-style-type: none"> <li>□ Oval NS 1 – 10</li> <li>□ Round NS 2 – 20</li> </ul> </li> <li>■ LipuJet-S <ul style="list-style-type: none"> <li>□ Oval NS 1 – 10</li> <li>□ Round NS 2 – 20</li> </ul> </li> <li>■ LipuSmart-P <ul style="list-style-type: none"> <li>□ Oval NS 1 – 10</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>■ For electronic measurement of layer of grease</li> <li>■ Suitable for liquid and/or congealing grease</li> <li>■ Measuring device with plug and used connecting cable, length: 3 m</li> <li>■ With two voltage-free changeover contacts to display full warning (80 %) and advance warning of fill level (50 %)</li> <li>■ With visual display of fill level</li> <li>■ With heated probe rod to increase reliability of operation</li> <li>■ Operating voltage: 230VAC/5 VA</li> <li>■ Max consumption approx. 12 W</li> <li>■ Weight: 2.8 kg</li> </ul>	<b>3300.11.50</b>
	Connection box		<ul style="list-style-type: none"> <li>■ Weight: 10 kg</li> </ul>	<b>7601.80.24</b>

You can find further accessories under → </38208542>