

LipuJet-P-OD

Product information for the product group



ACO Product benefits



- With two inspection windows for sludge and grease control
- Optionally with filling device
- Optionally with grease level sensor

- Grease separator according to EN 1825 for installation inside frost-free rooms
- Manufactured of polyethylene in oval shape
- Two covers odour-proof Ø 450 mm
- Inlet and outlet Ø 200 mm (NS 15 – 25) or Ø 250 mm (NS 30)
- Two inspection windows with wiper
- Operating side left or right

Item Technical Data 3815.45.42

Nominal capacity	Contents			Operation side
	Sludge trap [l]	Grease store [l]	Overall [l]	
NS 15	1580	630	2850	Right-hand


Dimensions



Nominal capacity	Dimensions					
	L1 [mm]	H1 [mm]	H2 [mm]	H3 [mm]	H4 [mm]	W2 [mm]
NS 15	2700	1850	1640	1300	1230	1340

Accessories

	Description	Used with	Description	Item number
	Grease layer thickness measuring device	<ul style="list-style-type: none"> ■ LipuJet-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuJet-S <ul style="list-style-type: none"> □ Oval NS 1 – 10 □ Round NS 2 – 20 ■ LipuSmart-P <ul style="list-style-type: none"> □ Oval NS 1 – 10 	<ul style="list-style-type: none"> ■ For electronic measurement of layer of grease ■ Suitable for liquid and/or congealing grease ■ Measuring device with plug and used connecting cable, length: 3 m ■ With two voltage-free changeover contacts to display full warning (80 %) and advance warning of fill level (50 %) ■ With visual display of fill level ■ With heated probe rod to increase reliability of operation ■ Operating voltage: 230VAC/5 VA ■ Max consumption approx. 12 W ■ Weight: 2.8 kg 	3300.11.50
	Grease layer thickness measuring device Multi Control		<ul style="list-style-type: none"> ■ To determine the disposal intervals of grease separators ■ Suitable for liquid and/or hardened fats ■ Delineation with colour-touch-panel ■ Continuous measure in percent ■ With integrated SD-card (4GB) for recording of the measuring process ■ With headed sounding stick (temperature is adjustable) to increase the operation safety ■ Three free of potential contacts for output of pre-alarm (adjustable), full-alarm (adjustable) and error ■ Measuring stick with adjusting scale ■ Delineation with plug-in cable connection, 3 m ■ Service voltage: 100 240VAC 50/60 Hz, 2 A ■ Power: ca. 43 W 	
		LipuJet-P LipuJet-S LipuSmart-P	Weight: 2.7 kg	3300.12.50

	Description	Used with	Description	Item number
	Heating rod	<ul style="list-style-type: none"> ■ Grease separators 	<ul style="list-style-type: none"> ■ To liquefy grease layer ■ Incl. control ■ Electrical connector <ul style="list-style-type: none"> □ 400 V/50 Hz/6.0 kW ■ Weight: 15 kg 	7300.01.00

You can find further accessories under → [/38154542](#)